



QE341 SCALPING SCREEN PIONEERING SOLUTIONS FOR YOU

TECHNICAL SPECIFICATION

The new QE341 represents the most advanced and complete mobile scalper yet designed. Customer feedback has been an integral element in the development of this model and the most sought-after features have been incorporated into this unit.

Our goal of minimum user intervention means that we have focused on delivering huge stockpiling capacity, with ease of stockpile removal, uninhibited material flow and ability to handle the toughest of material with an apron feeder fitted as standard. The 16' x 5' / 4.7 x 1.5 m screen box is highly aggressive with 9mm throw operating at over 1000 RPM. This ensures that even the most difficult materials can be handled effectively.

Whether it's working before or after a primary crusher or as a stand alone unit, the QE341 is designed to deliver high production with clean separation, the exceptional on-board conveyors ensure that the delivery is in harmony with the throughput. Applications include screening quarry overburden, blasted rock, landfill mining, C&D waste, aggregates, slag heaps, environmental clean-ups and topsoil/subsoil.

KEY BENEFITS

- Highly efficient easy-to-use electrical control system with colour coded push buttons for ease of use.
- Optimised material flow with no bottle necks.
- Heavy duty crusher-type chassis designed to accommodate interchangeable side conveyors and compatible for 2-way or 3-way split configurations.
- Large capacity wear resistant hopper with one-piece hopper design to minimise set-up time.
- Optional hydraulically folding wing extensions for increased feed width.
- Spacious and easily accessible hydraulically folding maintenance platforms fitted for ease of service.
- Highly flexible with the choice of different Sandvik screening media.
- Massive stockpiling capability through integrated hydraulic conveyors.
- Continuity with previous models and compatibility with QE440 ensures maximum uptime and optimisation of spare and wear parts stock
- Radio controlled tracks fitted as standard.
- Machine designed for efficient fuel economy and lowest operating cost per tonne.



KEY SPECIFICATIONS	QE341
Hopper	
Width	2574 mm / 8' 4"
Length	4160 mm / 13' 7"
Capacity	7.0 m ³ / 9.1 yd ³
Type	NEW rigid one-piece hopper
Feeder	
Width	1364 mm / 54"
Type	Steel apron standard
Oversize conveyor	
Width	1400 mm / 55"
Length (crs)	6270 mm / 27' 2"
Discharge height	4000 mm / 13' 1"
Angle adjustable	16° to 24°
Side conveyor (midsize)	
Width	800 mm / 32"
Length (crs)	8400 mm / 27' 7"
Discharge height	4059 mm / 13' 4"
Side conveyor (fines)	
Width	800 mm / 32"
Length (crs)	8270 mm / 27' 2"
Discharge height	4238 mm / 13' 11"
Transfer conveyor	
Width	1200 mm / 47"
Length (crs)	4300 mm / 14' 1"
Screen box	
Type	2 Bearing
Decks	2 Deck
Top deck	4700 x 1446 mm / 15' 5" x 4' 9"
Bottom deck	4200 x 1426 mm / 13' 9" x 4' 8"
Variable screen angles	11° - 17°

OPTIONS

Central auto lube (conveyors / screen)
 Remote diesel pump
 Water pump inc spray bars (mids and fines)
 -20°C (-4°F) Arctic package
 -30°C (-22°F) Arctic package
 Mesh on top deck
 Mesh on bottom deck
 Punch plate onto top deck tines
 Wear resistant liners in hopper & side conveyor feed boots
 Pull cords on all conveyors
 Canvas covers and brackets (mids and fines)
 Dust suppression spray bars (mids and fines)
 Lighting masts
 Punch plate on top deck

KEY SPECIFICATIONS	QE341
Tracks	
Length (crs)	3310 mm / 10' 10"
Width	400 mm / 16"
Power pack	
Engine type	CAT C4.4 74.5 kW / 100 hp CAT 4.4 83 kW / 111 hp
Diesel tank size	230 litres / 61 USG
Hydraulic tank size	460 litres / 122 USG
Transport dimensions	
Length	14.84 m / 48' 8"
Width	3.00 m / 9' 10"
Height	3.40 m / 11' 2"
Operating dimensions	
Length	15.44 m / 50' 7"
Width	14.51 m / 47' 7"
Height	4.49 m / 14' 7"
Standard weight	29,770 kg / 65,631 lbs
Performance	
Max feed size	600 mm ³ / 24"
Capacity (up to)	500 mtph / 551 stph
Travel speed	1 km/h / 0.62 mph
Max incline / Side to side	20° / 10°

Note. All weights and dimensions are for standard units only