



SANDVIK QH441 MOBILE CONE CRUSHER

TECHNICAL SPECIFICATION

The QH441 is the largest Sandvik Q-Range mobile cone crusher, designed for versatility, safety and high performance. Featuring the market leading Sandvik CH440 cone crusher, it comes with a number of features to ensure maximum uptime and minimum operator intervention.

KEY BENEFITS

Reliability	<ul style="list-style-type: none">- Market leading Sandvik CH440 cone for strength and high performance- Cone crusher unibody mainframe ensures optimal strength and less maintenance- Premium components selected throughout and FEA analysis on structural parts for durability- Up-and-over metal detector for stable and controlled detection- Steel pipe work used extensively to give superior heat dissipation and maximum reliability- Capable of operating in the most hostile environments
Productivity	<ul style="list-style-type: none">- Hydraulic cone Hydroset™ setting (CSS) and overload protection for maximum uptime- Superior power transfer resulting in tighter close side settings, and larger throw variations for precision crushing- Load sensing system for feeder drive, camera and level sensor ensure continuous crushing- Choice of chambers, throws and settings to optimize crusher for a wide range of applications- Full PLC control system with colour screen allowing visual data output & push button adjustment of all plant operating parameters- Available with single deck hanging screen to provide a 1 or 2 way split (see separate document for full specification)
Cost of ownership	<ul style="list-style-type: none">- Latest generation fuel efficient engines provide maximum performance and cost efficiency- Fluid clutch drive for smoother power transmission for optimum fuel efficiency and maximum power transfer- Well-proportioned fuel tank to maximize intervals between refueling- Unique Constant Liner Performance (CLP) for extended life of chamber liners, minimizing downtime and cost
Safety	<ul style="list-style-type: none">- Remote camera viewing the crushing chamber ensures full visibility without the need to access the machine- Superb access around the crusher for easy maintenance, especially during liner changes- Mandatory audible and visual warning for safe operation whilst tracking and start-up / shut down- Emergency stop buttons and conveyor pull stop cords around the plant for easy access during operation- Wireless radio handset and proportional speed control for safe tracking onsite- Spacious platforms provide safe access for service and maintenance- Dust suppression spray bars and onboard water pump to minimize dust improving operator and onsite safety
Support	<ul style="list-style-type: none">- Connected to Sandvik My Fleet with 7 year data subscription. Benefits include 24/7 fleet management, geo-fencing and remote operator support- Extensive global distributor network- Global aftermarket support, with standard stock parts to ensure minimum loss of production





KEY SPECIFICATIONS	QH441
Hopper	
Capacity	6.3 m ³ / 8.25 yds ³
Capacity with extensions	10.2 m ³ / 13.3 yds ³
Rear loading height	3.49 m / 11' 5"
Rear loading height (door lowered)	3.09 m / 10' 1"
Feed conveyor	
Belt width	1.20 m / 47"
Drive	Hydraulic variable speed
Metal detector type	Bridge coil
Main conveyor	
Belt width	1.20 m / 47"
Discharge height	3.73 m / 12' 3"
Crusher	
Cone	Sandvik CH440 cone
Speed	327 rpm to 346 rpm
Feed opening	215 mm / 8.5"
CSS range	8 - 48 mm / 5/16" - 1 7/8" *
Drive	Wet clutch with PTO
Lubrication tank	
Capacity	250 litres / 66 USG

KEY SPECIFICATIONS	QH441
Tracks	
Length (centres)	3.71 m / 12' 2"
Width (shoe)	500 mm / 20"
Control	Radio / Umbilical
Power pack	
Engine	CAT C13 Stage 5 / T4F 340 kW / 456 hp CAT C13 T3 328 kW / 440 hp
Diesel tank capacity	990 litres / 262 USG
Hyd tank capacity	990 litres / 262 USG
Transport dimensions	
Length	17.21 m / 56' 5"
Width	2.95 m / 9' 8"
Height	3.80 m / 12' 5"
Standard weight	51,242 kg / 112,969 lbs
Operating dimensions	
Length	16.56 m / 54' 4"
Width	3.32 m / 10' 10"
Height	4.91 m / 16' 1"
Performance	
Maximum feed size	215 mm / 8.5"
Capacity (up to)	388 tph / 435 stph *
Travel speed	0 - 1.3 km/h / 0 - 0.8 mph
Max incline / Side to side	20° / 10°

Note. All weights and dimensions are for standard units only

STANDARD SPECIFICATION

Feed hopper with wear resistant liner
 Folding hopper extensions for rear loading
 Main conveyor complete with dust covers
 Tool kit
 Light mast and cabinet lights
 Pull stop cords
 Camera on crusher feed hopper
 Level sensor on crushing chamber
 Dust suppression spray bars
 Over and under metal detector
 Remote diesel pump
 Radio control tracking, proportional
 Hydraulic water pump
 Hydraulic jacking legs
 My Fleet telematics

For option availability please speak with your local Sandvik representative

* Application specific. Please contact a Sandvik representative for clarification on specifications and options
 Sandvik reserves the right to make changes to the information on this data sheet without prior notification to users