



SANDVIK UH316 WHEELED CONE UNIT

TECHNICAL SPECIFICATION

The UH316 is a secondary/tertiary crushing unit fully assembled on a single trailer frame. Featuring the highly reliable and productive CH430 cone crusher and new SA1853 three deck vibrating screen for increased screening accuracy and efficiency, this model has been designed to offer high-end productivity processing 1- 3 products at a low cost-per-tonne.

KEY BENEFITS

Reliability	<ul style="list-style-type: none"> - Market leading Sandvik CH430 cone for strength and high performance - All onboard components are electrically driven giving reliability and minimal maintenance - Heavy duty chassis beams, strength analysis on structural parts and quality components for durability - Capable of operating in the most hostile environments
Productivity	<ul style="list-style-type: none"> - Large feed opening for increased intake ability and reduced bridging - Cone Crusher Unibody mainframe ensures optimal strength and less maintenance - Hydraulic cone Hydroset™ setting (CSS) and overload protection for maximum uptime - Constant Liner Performance (CLP) crushing chambers permits constant feed acceptance capability, increased output, high quality products and increased liner life - Choice of several chambers, throws and settings for a wide range of applications, enabling fine tuning to your specification and improved capacity - New SA screen with improved performance and screening accuracy, built for durability and ease of operation - Simple and efficient operation with soft starting crusher for trouble free operation
Cost of ownership	<ul style="list-style-type: none"> - Low cost per tonne due to electric operation - Quick to set-up and easy to maintain, resulting in more uptime and higher productivity
Safety	<ul style="list-style-type: none"> - New screen has been designed for enhanced safety with a protected steel coil spring and PU end cup as standard - Removable electrical control panel can be located on the ground during operation - Crusher mounted safety guards and multiple emergency stop buttons for safe operation - Maintenance platforms with handrails and access ladders provide excellent access for service and maintenance
Sustainability	<ul style="list-style-type: none"> - Low emissions due to electrical operation, reducing CO₂ emissions - Screen design gives longer wear life of components - Quality components ensure longer lifetime and support optimized service and maintenance





KEY SPECIFICATIONS	UH316
<hr/>	
Screen	
<hr/>	
Type	Sandvik SA1853 circular motion
Decks	3 deck
Size	1829 mm x 4877 mm / 6' x 16'
Drive	Electric motor 18.5 kW
<hr/>	
Crusher	
<hr/>	
Type	Sandvik CH430 cone
Adj type	Hydraulic
CSS range	6 - 41 mm / ¼ - 1 ½" *
ASRi	Optional
Drive	Electric motor 132 kW, 4 pole
<hr/>	
Power system	
<hr/>	
All electrics are intended for connection to a mains supply	
<hr/>	
Total power	159.5 kW
Supply voltage	415-50 Hz / 440 V-60 Hz / 3-phase AC
Control voltage	220V-50 / 60 Hz / 3-phase AC
<hr/>	
Running gear	2" / 3 1/2" King-pin, double-axle bogie with air-brakes and running lights. Tyres 10" x 20" - 16 ply

If powered by a genset at least 350 KVA is required

KEY SPECIFICATIONS	UH316
<hr/>	
Transport dimensions	
<hr/>	
Height	5.0 m / 16.40'
Width	2.8 m / 9.18'
Length	12.30 m / 40.35'
Weight	35,000 kg / 77,161 lbs
<hr/>	
Operating dimensions	
<hr/>	
Height	7.77 m / 25.49'
Width	4.34 m / 14.23'
Length	11.80 m / 38.71'
<hr/>	
Performance	
<hr/>	
Max feed size	214 mm / 8.42"
Capacity (up to)	250 mtp / 275 stph *

Note. All weights and dimensions are for standard units only

STANDARD SPECIFICATION

Self contained electrical switchgear cabinet with soft starter
Maintenance platform with handrails and access ladder
Safety guards to crusher drives
Emergency stop buttons
2" / 3 1/2" King-pin, double-axle bogie with air-brakes and running
lights. Tyres 10" x 20" - 16 ply
Trailer suitable for 24 V supply

For option availability please speak with your local Sandvik representative

* Application specific. Please contact a Sandvik representative for clarification on specifications and options
Sandvik reserves the right to make changes to the information on this data sheet without prior notification to users