



# SANDVIK UH373 WHEELED CONE CRUSHER

## TECHNICAL SPECIFICATION

The UH373 is an open circuit crushing unit fully assembled on a single triple axle trailer frame. Featuring the highly reliable and powerful CH440 cone crusher and a number of different feed and discharge conveyors variants, the unit comes with a control panel for smooth and easy operation of the unit. This model has been designed to offer high-end productivity processing at a low cost-per-tonne.

### KEY BENEFITS

<b>Reliability</b>	<ul style="list-style-type: none"> <li>- Market leading Sandvik CH440 cone for strength and high performance</li> <li>- All onboard components are electrically driven giving reliability and minimal maintenance</li> <li>- Heavy duty chassis beams, strength analysis on structural parts and quality components for durability</li> <li>- Capable of operating in the most hostile environments</li> </ul>
<b>Productivity</b>	<ul style="list-style-type: none"> <li>- Largest feed opening in its class for increased intake ability and reduced bridging</li> <li>- Hydraulic cone hydrosset setting (CSS) and overload protection for maximum uptime</li> <li>- Cone Crusher Unibody mainframe ensures optimal strength and less maintenance</li> <li>- ASRiT<sup>™</sup> automatically adapts crusher to feed conditions and enables real-time performance management</li> <li>- Constant Liner Performance (CLP) crushing chambers permits constant feed acceptance capability, increased output, high quality products and increased liner life.</li> <li>- Choice of several chambers, throws and settings for a wide range of applications, enabling fine tuning to your specification and improved capacity</li> <li>- Simple and efficient operation with soft starting crusher for trouble free operation</li> <li>- Metal detector on crusher feed conveyor</li> </ul>
<b>Cost of ownership</b>	<ul style="list-style-type: none"> <li>- Quick to set-up and easy to maintain, resulting in more uptime and higher productivity</li> <li>- Low cost per ton due to electric operation and Sandvik chamber design</li> </ul>
<b>Safety</b>	<ul style="list-style-type: none"> <li>- Removable electrical control panel to be located on the ground during operation</li> <li>- Crusher mounted safety guards and multiple emergency stop buttons for safe operation</li> <li>- Maintenance platforms with handrails and access ladders provide excellent access for service and maintenance</li> </ul>
<b>Sustainability</b>	<ul style="list-style-type: none"> <li>- Low emissions due to electrical operation, minimizing environmental impact</li> <li>- Quality components ensure longer lifetime and supports optimized service and maintenance</li> </ul>
<b>Support</b>	<ul style="list-style-type: none"> <li>- Extensive USA distributor, sales and service network</li> <li>- Manufactured in America</li> </ul>





KEY SPECIFICATIONS	UH373
<b>Crusher</b>	
Type	Sandvik CH440 cone
Adj type	Hydraulic
CSS range	5/16" - 1 7/8" / 8 - 48 mm *
Control System	ASRI - Standard
Drive	Electric motor 300 hp
<b>Crusher feed conveyor</b>	
Belt width	36" / 915 mm
Drive	20 hp / 1800 rpm
<b>Crusher discharge conveyor</b>	
Belt width	42" / 1,067 mm
Drive	15 hp / 1800 rpm

KEY SPECIFICATIONS	UH373
<b>Power system</b>	
All electrics are intended for connection to a mains supply	
Total Power	335 hp
Supply voltage	460 V-60 Hz / 3 phase AC
Control voltage	110 V-60 / 3 phase AC
<b>Running gear</b>	
2" king-pin, triple axle suspension with air-brakes lights and mud flaps. Tyres 11' x 22.5'	
<b>Transport dimensions</b>	
Length	64' 6 5/16" / 19.67 m
Width	11' 11 1/8" / 3.64 m
Height	13' 11 9/16" / 4.26 m
Standard weight	100,000 lbs / 45,359 kg
<b>Operating dimensions</b>	
Length	63' 3 5/8" / 19.29 m
Width	19' 1 1/4" / 5.82 m
Height	18' 2 1/2" / 5.55 m
<b>Performance</b>	
Max feed size	8.5" / 215 mm
Capacity (up to)	385 stph / 350 mtph

Note. All weights and dimensions are for standard units only

## STANDARD SPECIFICATION

All conveyors fitted with mining duty reducers, bearings and CEMA idlers  
 Remote grease lines for conveyors  
 Overflow discharge chute on cone ring  
 UL certified removable electrical switchgear  
 Soft starter for cone crusher  
 Six hydraulic levelling legs with gas hydraulic power unit  
 (1) Hydraulic conveyor raise / lower (Feed conveyor)  
 (1) Hydraulic conveyor pivot (Feed conveyor)  
 (9) E-stop buttons in the unit

Number of conveyor feeding and discharge options  
**Rear feed rear discharge**  
 Left or right side mounting of feed conveyor  
 Feed conveyor hydraulically raised/lowered during transport  
 Feed conveyor pivot frame – slide in slide out done hydraulically  
**Rear discharge**  
**Rear feed side discharge**  
 Feed conveyor hydraulically raised/lowered during transport  
 Side discharge conveyor discharge either side – left or right  
**Rear feed front discharge**  
 Feed conveyor hydraulically raised/lowered during transport

For option availability please speak with your local Sandvik representative

\* Application specific. Please contact a Sandvik representative for clarification on specifications and options  
 Sandvik reserves the right to make changes to the information on this data sheet without prior notification to users