



SANDVIK UH440i MOBILE CONE CRUSHER

TECHNICAL SPECIFICATION

The UH440i is a high quality, tracked mobile cone crusher that is robust and built to last. This heavy duty workhorse has proved itself worldwide in the toughest of applications and in all climatic conditions. Featuring the CH440 crusher and an automated onboard "intelligence" system, this results in optimal performance, less downtime and better productivity.

KEY BENEFITS

Reliability	<ul style="list-style-type: none">- Built for hard and abrasive rock- Proven technology combined with Sandvik CH440 cone for strength and high performance- Rubber lined feed hopper and impact zones for longevity, as well as protection from wear and noise- Premium quality components for durability
Productivity	<ul style="list-style-type: none">- ASRi assists in optimizing throughput and end product quality, as well as protecting the crusher from "uncrushable" material- Level sensors and step less regulation of feed belt for optimized production- Onboard intelligence system for optimal performance and operating efficiency. Integrated with ASRi- A number of sensors at different key locations to ensure a trouble free operation and prevent costly breakdowns- Choice of several chambers, throws and settings for a wide range of applications, enabling fine tuning to your specification and improved capacity- Quick to set-up and easy to transport, resulting in more uptime and higher productivity- The unit can work as stand alone or interlocked in a "process train" with other crushing and screening units- Hanging screen available for open and closed circuit
Cost of ownership	<ul style="list-style-type: none">- Direct drive, heavy duty fluid coupling and low rpm engine for fuel-efficient operation- Quick return on investment and high resale value- Unique Constant Liner Performance (CLP) for extended life of chamber liners, minimizing downtime and cost
Safety	<ul style="list-style-type: none">- User-friendly control system via PLC from one location and radio remote control as standard- Dust suppression spray bars and dust sealed conveyor minimize dust, improving operator and onsite safety- Minimal maintenance with safe and easy access- No oil spillage during filter changes due to vacuumized hydraulic system- LED Floodlights for safe operation 24 hours a day
Support	<ul style="list-style-type: none">- Connected to Sandvik My Fleet with 7 year data subscription. Benefits include 24/7 fleet management, geo-fencing and remote operator support- Extensive global distributor network- Operational advice through our process knowledge and expertise





KEY SPECIFICATIONS	UH440i
Hopper	
Width	2930 mm / 9' 7"
Length	4000 mm / 13'
Nominal capacity	6 m ³ / 7.85 yds ³
Rear loading height	3350 mm / 10' 11"
Rear loading height (door lowered)	3150 mm / 10' 3"
Feed conveyor	
Belt width	1200 mm / 47"
Drive type	Hyd - variable speed
Metal detector type	Bridge coil
Crusher	
Type	Sandvik CH440 Cone
Feed opening	215 mm / 8.5"
CSS range	8 - 48 mm / 5 / 16" - 1 7/8" *
Chamber control	Sandvik Hydroset system (ASRI)
Speed	320 rpm
Drive	Direct drive via fluid coupling
Main conveyor	
Belt width	1400 mm / 55"
Discharge height	4050 mm / 13' 3"

KEY SPECIFICATIONS	UH440i
Power pack	
Type	Volvo D13
Stage / Tier	Stage 5 / T4F / T2 CAT T3 (optional)
Engine power	315 kW / 422 hp
Diesel tank capacity	1125 litres / 297 USG
Hyd tank capacity	415 litres / 110 USG
Lubrication tank capacity	245 litres / 64.7 USG
Tracks	
Length (centres)	4170 mm / 13' 8"
Width (shoe)	500 mm / 20"
Drive	Hydraulic
Control	Radio / Umbilical
Transport dimensions	
Length	18.77 m / 61' 7"
Width	3.0 m / 9' 10"
Height	3.89 m / 12' 9"
Weight	48,000 kg / 105,822 lbs
Operating dimensions	
Length	17.40 m / 57'
Width	3.0 m / 9' 10"
Height	4.9 m / 16'
Weight	48,975 kg / 107,972 lbs
Performance	
Max feed size	215 mm / 8.5"
Capacity (up to)	400 mtp/h / 440 stph *
Traveling speed	1.2 km/h / 0.75 mph
Max incline / side to side	20° / 10°

Note. All weights and dimensions are for standard units only

STANDARD SPECIFICATION

- Rubber lined hopper
- Auto speed controlled feed conveyor
- Metal detector
- Crusher level sensor
- Pressurised cone dust protection
- ASRI cone control system
- Heavy duty main conveyor with dust covers
- 24v canbus PLC control system
- Pre-heating for engine and cone lube systems
- Electric refuelling pump
- Light mast, warning beacons, panel light and tracking lights
- Radio remote control with umbilical cord as back-up
- Vacuum pump for maintenance
- Walkways and ladders
- Tool kit
- Dust suppression spray bars on crusher and main conveyor discharge
- My Fleet telematics
- Main conveyor stockpile level sensor

For option availability please speak with your local Sandvik representative

* Application specific. Please contact a Sandvik representative for clarification on specifications and options
Sandvik reserves the right to make changes to the information on this data sheet without prior notification to users